CHEM Master® 2000 (749)

1. Product And Company Identification

Borealis Compounds Inc 176 Thomas Road Port Murray, NJ 07865

Telephone Number: (908) 850-6200

Emergency Contacts/Telephone Numbers

William E Wallace Emergency Phone Number: (908) 850-6243

Issue Date: 05/12/2011

Product Name: LE4460 (26048)

Chemical Type: Mixture

CHEM Master® Number: 10150

MSDS Number: 127

2. Composition/Information On Ingredients

Antimony Trioxide (1309-64-4) 5.000 - 40.000 % Proprietary Brominated Aromatic 40.0000 - 85.0000 %

3. Hazards Identification

Emergency Overview

Vapors from materials heated above the decomposition temperature > 300°C may be toxic, irritating and possibly corrosive.

Primary Routes(s) Of Entry

Inhalation of dusts and vapors from heated material may be irritating to respiratory system and eyes.

Eve Hazards

Vapors from heated materials may cause eye irritation. Contact with heated materials may cause thermal burns.

Skin Hazards

Contact with heated materials may cause thermal burns.

Ingestion Hazards

Not a normal route of exposure. However, if ingested may cause gastrointestinal disturbances. Contact with heated materials may cause thermal burns.

Inhalation Hazards

Dust and vapors from heated materials may cause respiratory tract irritation.

4. First Aid Measures

Eye

Flush eyes immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. If irritation persists, get medical attention. Thermal burns to the eyes or area around the eyes require immediate medical attention.

Skin

Wash area of contact thoroughly with soap and water. If burned form contact with hot material, flush skin immediately with large amounts of cool water and get medical attention. If irritation persists, get medical attention. Thermal burns require immediate medical attention.

Ingestion

Get medical attention immediately.

Inhalation

Remove affected person from the source of exposure to an area of fresh air. Get medical attention if irritation persists or breathing becomes difficult.

MATERIAL SAFETY DATA SHEET MSDS #: 127 LE4460 (26048)

5. Fire Fighting Measures

Flash Point: NA °C

Autoignition Point: >300 °C Flammability Class: NA Lower Explosive Limit: NA Upper Explosive Limit: NA

Fire And Explosion Hazards

Dust laden condition increase potential for fire and explosion.

Extinguishing Media

Use dry chemical, foam or water spay to extinguish fire. Use water spay to cool fire exposed containers, structure and to protect personnel. Do not flush down public sewers or drainage systems.

Fire Fighting Instructions

Irritating or toxic substances may be emitted upon thermal decomposition. Exposed fire fighters should wear NIOSH approved self-contained breathing apparatus with full-face mask and full-fire fighting protective clothing.

6. Accidental Release Measures

No special procedures are required for clean-up of spills or leaks of this material. Avoid methods that result in water pollution or generation of dust. Caution should be exercised regarding personal safety and exposure to the spilled material.

7. Handling And Storage

Handling Precautions

Avoid prolonged or repeated contact with skin or clothing. If contact is unavoidable, wear protective clothing, face protection and gloves. Use with adequate ventilation. Wear gloves capable of resisting >200°C. Contact with molten material may cause thermal burns.

Storage Precautions

Store in cool dry location.

Work/Hygienic Practices

After handling, wash thoroughly with soap and water.

8. Exposure Controls/Personal Protection

Eye/Face Protection

Safety glasses should be worn during handling of product.

Skin Protection

Wear clothing and gloves to avoid unnecessary contact with the product. When working with molten product, wear gloves capable of resisting a temperature >200°C.

Respiratory Protection

Wear NIOSH approved respirators in accordance with OSHA regulations when necessary.

9. Physical And Chemical Properties

Appearance

White pellets.

Odor

Slight odor.

Chemical Type: Mixture Physical State: Solid Melting Point: >100 °C Boiling Point: NA °C Specific Gravity: 2

MATERIAL SAFETY DATA SHEET MSDS #: 127

LE4460 (26048)

9. Physical And Chemical Properties - Continued

Vapor Pressure: NA Vapor Density: NA pH Factor: NA

Solubility: Insoluble in water

Viscosity: NA

Evaporation Rate: NA

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Avoid contact with strong oxidizing agents and elevated temperatures.

Incompatible Materials

Oxidizers

Hazardous Decomposition Products

Material will slowly decompose at temperatures >300°C. Thermal decomposition may release acrid smoke and irritating vapors. Hazardous decomposition accelerates above 500°C ultimately releasing gases of bromine.

Conditions To Avoid (Polymerization)

Elevated temperatures.

11. Toxicological Information

This product has not been tested as a whole for all potential health effects. It may have other health hazards relating to its components.

12. Ecological Information

Acute Toxicity - Fish And Invertebrates

NA

Toxicity - Aquatic And Terrestrial Plants

NA

Acute And Dietary Toxicity - Birds

NΑ

Toxicity - Beneficial Microoranisms

NA

13. Disposal Considerations

This substance, when discarded or disposed of is not specifically listed as a hazardous waste in Federal regulations. However, it could be hazardous if it is considered toxic, corrosive, ignitable or reactive according to Federal definitions (40 CFR 261). Additionally, it could be designated as hazardous waste if it is mixed with or comes in contact with a hazardous waste. If such contact or mixing may have occurred, check 40 CFR 261 to determine whether it is a hazardous waste.

The transportation, storage, treatment and disposal of this waste material must be conducted in accordance with all applicable Federal, state and local regulations.

RCRA Information

NA

14. Transport Information

No Data Available...

MATERIAL SAFETY DATA SHEET MSDS #: 127

LE4460 (26048)

14. Transport Information - Continued

Proper Shipping Name

Plastic Granules Non-Hazardous

Hazard Class

NA

DOT Shipping Label

NA

Freight Class

NA

Packaging Exceptions

Packaging Requirements

NA

15. Regulatory Information

U.S. Regulatory Information

All ingredients within this product meet TSCA regulations.

16. Other Information

NFPA Hazard Rating

Health: 1 Fire: 1 Reactivity: 0

HMIS Hazard Rating

Health: 1 Fire: 1 Reactivity: 0

Revision/Preparer Information

MSDS Preparer: Gary Gerlach

MSDS Preparer Phone Number: (908) 850-6254

This MSDS Superceeds A Previous MSDS Dated: 07/22/2009

Reference Documentation

Material Specification Sheet Reference

The product(s) mentioned herein are not intended to be used for medical, pharmaceutical or healthcare application and we do not support their use for such applications.

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borealis makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantabiltiy or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borealis' products in conjunction with other materials. the information contained herein exclusively to our products when not used in conjunction with any third party materials.

MATERIAL SAFETY DATA SHEET MSDS #: 127 LE4460 (26048)

16. Other Information - Continued

Borealis Compounds Inc